WAC LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

2.5" Low Voltage

New Construction Non-IC Housing

Model & Product

❍ HR-802 2.5in Low Voltage New Construction Non-IC Housing

Example: **HR-802**

DESCRIPTION

Superb performance delivered in a small package. The 2.5" Low Voltage Recessed Downlight series offers smooth and crisp light for under cabinet and tight recessed spaces where miniature apertures are desired. May be used with any WAC compatible 2.5" HR-837, HR-834, or HR-836 trims.

FEATURES

- 3" clearance on all sides when insulation is present
- Total depth of 4", one of the lowest profile recessed units available
- Low profile housing
- Transformer included
- 5 year warranty

SPECIFICATIONS

Construction:	20 gauge steel
Power:	50W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-10%
Light Source:	Halogen MR16
Mounting:	Supplied with hanger bars, adjustable from 15"-242" to accommodate various joist construction and grid sizes.
Cut Out:	3"
Ceiling Thickness:	3/4"
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Damp Location Listed, Non IC

LINE DRAWING:



WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. December 2021

WAC LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

2.5" Low Voltage

Downlight Trim

Model & Light Source	Lumens	Finish
❍ HR-836 Halogen MR16 ❍ HR-836LED LED MR16		❍ BN Brushed Nickel ❍ CB Copper Bronze ❍ WT White

Example: **HR-836-BN**

DESCRIPTION

Superb performance delivered in a small package. The 2.5" Low Voltage Recessed Downlight series offers smooth and crisp light for under cabinet and tight recessed spaces where miniature apertures are desired. For use with HR-800 series low voltage housings. Accepts MR16 LED or incandescent lamp 50W max, housing and lamp are sold separately.

FEATURES

- Accommodates most LED MR16 or Halogen MR16 lamps
- Retention clips secure lens firmly to lamp
- Clear lens included, replaceable lens options available
- 5 year warranty

SPECIFICATIONS

Construction:	20 gauge steel with die-cast aluminum baffle
Light Source:	Halogen MR16, LED MR16
Finish:	Electrostatically Powder Coated:White, Electrostatically Powder Coated::Copper Bronze, Electrostatically Powder Coated:::Brushed Nickel
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Damp Location Listed

FINISHES:

White | Copper Bronze | Brushed Nickel

LINE DRAWING:



WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. December 2021

WAC LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

2.5" Low Voltage

Adjustable Trim

Model & Light Source	Lumens	Finish
❍ HR-837 Halogen MR16 ❍ HR-837LED LED MR16		❍ BK Black ❍ BN Brushed Nickel ❍ CB Copper Bronze ❍ WT White

Example: **HR-837-BK**

DESCRIPTION

Superb performance delivered in a small package. The 2.5" Low Voltage Recessed Downlight series offers smooth and crisp light for under cabinet and tight recessed spaces where miniature apertures are desired. For use with HR-800 series low voltage housings. Accepts MR16 LED or incandescent lamp 50W max, housing and lamp are sold separately.

FEATURES

- Accommodates most LED MR16 or Halogen MR16 lamps
- Retention clips secure lens firmly to lamp
- Clear lens included, replaceable lens options available
- 5 year warranty

SPECIFICATIONS

Construction:	20 gauge steel
Light Source:	Halogen MR16, LED MR16
Finish:	Electrostatically Powder Coated:White, Electrostatically Powder Coated::Black, Electrostatically Powder Coated:::Copper Bronze, Electrostatically Powder Coated::::Brushed Nickel
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Damp Location Listed

FINISHES:



White | Black | Copper Bronze | Brushed Nickel

LINE DRAWING:



WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. December 2021